

# CCV OPP-C60

A safe investment



**Fast system and processor performance**



**High-resolution color display and big fonts for best readability**



**Processing of major bank- and fleet-cards**



<b>Display</b>	TFT color display, QVGA, 320x240 pixels, high luminosity, high contrast, graphics capability, fully visible at sunlight	<b>OPP-C60 Standard:</b> 3,5" diagonal	<b>OPP-C60 compact:</b> 2,7" diagonal
<b>RAM</b>	128 MB SDRAM, 256 MB Flash		
<b>Processor</b>	32-Bit ARM11, 533MHz		
<b>Dimensions</b>	<b>OPP-C60 Standard:</b> Eternal dimensions: 199 x 140 x 50 mm Panel: 160 x 101 mm Weight: 995 g	<b>OPP-C60 compact:</b> Eternal dimensions: 141 x 92 x 50 mm Panel: 120 x 82 mm Weight: 583 g	
<b>Keypad</b>	Vandal-proof stainless keypad in accordance with IK10, keys are raised above the front panel, abrasion-resistant laser engraved with tactile feedback, EBS-100 compliant		
	<b>OPP-C60 Standard:</b> 20 keys, of which 4 are configurable function keys	<b>OPP-C60 compact:</b> 16 keys	
<b>Communication/ Interfaces</b>	1x LAN, 2x USB (USB 2.0 OTG 480 MBit/s USB Mini-B, USB 2.0 Host 12 MBit/s USB-A), 4x RS232 (COM, SCR, POS, MDB), 2x SAM Optional: ISDN and GSM/GPRS external		
<b>Front panel</b>	Brushed stainless steel, vandal-proof, IP 65 if installed correctly, can be installed flush in terminal front panels up to 3 mm thick		
<b>Environmental conditions</b>	Operating temperature: -20°C - 70°C, 5% - 90% relative air humidity, non-condensing		
<b>Interfaces</b>	ZVT, O.P.I., MDB		
<b>Certifications</b>	Compatible with the current specifications DK TA7.2/DC POS 3.0, PCI-PTS 5.x, EMV, RoHS, CE, Mastercard Contactless, Visa Contactless, American Express Contactless, Diners Contactless		